Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants – Transmission Oils - Automotive

Version: 244/01 Valvoline[™] ATF Pro 236.15

Premium full synthetic high performance automatic transmission fluid for passenger cars, vans, LCV, SUV with Fuel Economy properties.

Valvoline ATF Pro 236.15 provides superior protection and lubrication of the automatic gearbox over a wide temperature range. The product's lower viscosity reduces the fuel consumption by easier flowing through the automatic gearbox and improving the shifting of the latest 7-G Tronic Plus transmission.

O.E.M. approvals

MB-Approval 236.15

Features and Benefits

Superior protection

Superior protection against wear and tear, also under high stress working conditions.

Advanced additives

Superior additives protect against corrosion, oxidation, foaming, and deposits.

Breakdown resistance

Premium synthetic base oils, balanced additive system avoid breakdowns and stick-slip even after long-time use.

Fuel Economy

Fuel Economy properties by means of lower viscosity, easier oil flow and lower resistance.

Consistent, stable viscosity

Superior viscosity-temperature properties even at very low temperatures. Highly stable viscosity over a long period.

Enhanced friction properties

Premium fully synthetic base oils, viscosity index improvers, and friction modifiers result in outstanding friction properties for smoother shifting. In addition, the product resists aging and has excellent thermal stability.

Performance levels

MB NAG-2+ transmissions MB 7-speed automatic transmission series Tronic Plus

Applications

Suitable for automatic gearboxes of passenger cars, vans, LCD, SUV when the manufacturer recommends an ATF according to MB 236.15

Can be used in MB 7-speed NAG-2+ transmissions.

Not suitable for other automatic transmissions. Not suitable for use as MB-236.10, 12, 14.



Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Safety Data Sheet (SDS) is available on request via your local sales office or via the internet @ http://msds.ashland.com

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline ATF Pro 236.15	
Colour	Blue
Viscosity , mm ² /s @ 100 °C.	4,4
DIN 51562-1	
Viscosity, mm²/s @ 40 ºC.	18,0
DIN 51562-1	
Viscosity Index	160
DIN ISO 2909	
Pour Point, °C	-48
DIN ISO 3016	
Specific Gravity @ 15.6°C.	0,841
DIN 51757	
Flash Point, COC, °C.	>180
DIN ISO 2592	

This information only applies to products manufactured in the following location(s): Europe

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife[™], the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com**

Author:

AdG Replaces –

™ Trademark of Ashland or its subsidiaries, registered in various countries [©] 2015, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.

